

Date of publication xxxx 00, 0000, date of current version xxxx 00, 0000.

Digital Object Identifier 10.1109/ACCESS.2017.DOI

Electrochemical Model and Sigma Point Kalman Filter based Online Oriented Battery Model

E. MIGUEL¹, GREGORY L. PLETT², M. SCOTT TRIMBOLI², I. LOPETEGI¹, L. OCA¹, U. IRAOLA¹, E. BEKAERT³

¹Mondragon Unibertsitatea, Electronic and computing department, 4 Loramendi, Mondragon 20500, Basque Country, Spain

²Department of Electrical and Computer Engineering, University of Colorado Colorado Springs, Colorado Springs, CO 80918, United States

³Centre for Cooperative Research on Alternative Energies (CIC energiGUNE), Basque Research and Technology Alliance (BRTA), Alava Technology Park, Albert Einstein 48, 01510 Vitoria-Gasteiz, Spain

Corresponding author: E. Miguel (e-mail: emiguel@mondragon.edu).

This work has been partially funded by a predoctoral grant of the Basque Government (PRE.2019.2.0195).

ABSTRACT This paper presents a reduced-order electrochemical battery model designed for online implementation of battery control systems. This model is based on porous-electrode and concentrated-solution theory frameworks and is able to predict voltage as well as the internal electrochemical variables of a battery. The reduction of the model leads to a physics-based one-dimensional discrete-time state-space reduced-order model (ROM) especially beneficial for online systems. Models optimized around different operational setpoints are combined in order to predict the cell variables over a wide range of temperature and state of charge (SOC) using the output-blending method. A sigma-point Kalman filter is further used in order to cope with inaccuracies generated by the reduction process and experimental-related issues such as measurement error (noise) on the current and voltage sensors. The state-estimation accuracies are measured against a full-order model (FOM) developed in COMSOL. The whole system is able to track the internal variables of the cell as well as the cell voltage and SOC with very high accuracy, demonstrating its suitability for an online battery control system.

INDEX TERMS Batteries, Battery management systems, Electrochemical devices, Kalman filters

I. INTRODUCTION

Energy storage systems (ESSs) are a key factor in the energetic transition that is presently taking place in the world. Due to the increasing demand for electric vehicles in the transport industry and for renewables in the energy-generation sector, the creation of efficient ESSs has become a challenge to overcome. One of the most promising types of energy storage uses lithium-ion batteries since their high power and energy densities meet the requirements of a wide variety of applications.

Due to the expense of lithium-ion batteries as well as finite raw-material resources, it is crucial to optimize battery life expectancy. Not only this, it is also key to optimize the power and available-energy capabilities of batteries while minimizing the rate of aging instead of the common approach of simply oversizing the ESS as a defense against overly rapid aging. With the aim of satisfying these objectives, battery management systems (BMSs) need to be enhanced. These BMSs run battery models to keep the battery in a

safe condition and to be able to estimate the SOC, state-of-health (SOH) and state-of-function (SOF), (a computation of limits on available power that seeks to maximize battery output power at the same time as maximizing battery service life). Presently, BMSs commonly use phenomenological empirically-based models such as equivalent-circuit models (ECM) that can make accurate estimates of the SOC of the batteries. However, these models do not describe the internal physical electrochemical variables of the battery and so it is impossible to use them to estimate how the battery is working internally, which is necessary to be able to predict aging phenomena. Thus, use of empirical models leads to a poor SOF prediction.

Other recent attempts take advantage of incipient artificial intelligence (AI) techniques, to estimate SOH and remaining useful life (RUL) [1]. The capabilities of these algorithms are highly dependent on the available data for the training process. Therefore even a very powerful tool to deal with the

effect of aging in state estimators, if internal states need to be computed, physics-based models (PBMs) are key, being the combination of PBMs and AI a promising field of research [2]–[4]. ROMs can be used in this context to feed AI algorithms efficiently, or to give feedback to the AI algorithms, while running in the BMS. Also AI techniques could be used to aid handling uncertainty in the predictions [5] or in model parameters [6].

Therefore, it is necessary to use physics-based models (PBMs) of the lithium-ion cells in an ESS. These models are based on equations developed from first-principles physics that describe the internal physical behavior of the battery cell. It is believed that with the insight that PBMs can give, the BMS can be programmed to predict the state of aging mechanisms occurring inside the battery cells and control the battery based on these predictions. This could enable determining the true energy and power capabilities of batteries accurately in real-time, avoiding oversizing. Furthermore, use of these models can enable managing battery service life to avoid undesirable aging effects.

Taking all these considerations into account a clear research gap can be inferred. It is a challenge to efficiently implement PBMs embedded in BMSs. Furthermore taking advantage of them to enable accurate SOF determination, whether it is working by their own or in combination with AI algorithms, is a key challenge. Last but not least experimental validation of these models is very important, since proof of their validity in real case scenarios is needed to finally validate the concept. Overcoming these challenges will potentially lead to more efficient use and longer life of a battery.

The main handicap to implementing PBMs in BMSs is that they have much higher computational complexity than empirical models and so powerful computational resources are required to use them. To deal with this drawback, model-order reduction methods can be applied, creating physics-based ROMs. ROMs are computationally simpler models that can predict the same internal physical variables. These ROMs can be executed in a practical BMS, and so battery controls based on the physical variable estimates can be designed.

A number of different research teams have studied the problem of reducing the computational complexity of PBMs [7]. Some approximate the original partial differential equations (PDEs) using analytic expressions leading to some well-developed simplification approaches. Subramanian *et al.* [8] found polynomial solutions for solid-phase diffusion under constant current (CC). This approximation approach was then extended to other PDEs, generating a group of differential algebraic equations (DAEs) to substitute the original PDEs [9]. Several other approaches were introduced by different researchers to generate simplified DAEs from the original PDEs, including the Galerkin method [10], [11], finite difference [12], [13], proper orthogonal decomposition [14], volume averaging [15], singular perturbation [16], and so forth.

A very different approach focuses on small-signal

frequency-domain characteristics of the original PDEs via deriving transfer functions for all cell internal electrochemical variables. These transfer functions are then used to yield a high-fidelity time-domain ROM, that has similar frequency response but a greatly simplified form compared with the FOM defined by the PDEs. These transfer functions are also derived starting with a description of the solid-diffusion process. Jacobsen and West gave the transcendental transfer function for solid concentration versus lithium flux in spherical symmetry [17]. Smith *et al.* built on this work to derive transfer functions for solid–electrolyte interphase potential difference, solid surface concentration, and lithium flux versus applied cell electrical current [18]. They then generated a low-order state-space model through a residue-grouping approach [19]. Inspired by their work, Lee *et al.* derived additional transfer functions for solid potential, electrolyte potential, and electrolyte concentration versus applied cell electrical current and proposed a novel discrete-time realization algorithm (DRA) to produce a reduced-order discrete-time state-space model of a lithium-ion battery cell [20], [21]. Rodriguez *et al.* proposed an improved derivation of the electrolyte-concentration transfer function [22] and extended the transfer functions to accommodate cells having blend electrodes [23]. Most recently, an improved high-fidelity model was introduced by removing a historic limiting assumption that the effect of electrolyte concentration on electrolyte potential could be ignored [24], and by replacing the DRA with computationally simpler methods that produce equivalent results [25].

DAE-based and transfer-function-based ROMs have distinct advantages and disadvantages. We prefer ROMs obtained through transfer functions for several reasons. Above all, the approach allows us to choose any combination of internal variables and spatial locations of interest to solve, rather than needing to solve for all of the variables at every location in the cell, which brings desirable freedom and computational simplicity. In addition, the online computational and storage efficiency is on the same order as an ECM because the transfer functions are converted into reduced-order discrete-time state-space models represented by low-order matrices. The computational complexity of the resulting ROM is very low, even though the conceptual complexity of the derivations to find the transfer functions and to develop the corresponding discrete-time realization may require more effort. The ROM can produce very high-fidelity approximations to the FOM, both for voltage predictions and for predictions of internal electrochemical variables.

This paper furthers the development of transfer-function-based ROMs in a number of ways: (1) A sigma-point Kalman filter (SPKF) is designed and implemented to keep the ROM state-variable estimates accurate in a real scenario, where some error sources need to be taken into account; (2) This SPKF maintains increased accuracy by using an output-blending technique to combine the dynamics of ROMs generated at different operational setpoints near to the present operating point; (3) The system comprising the ROM and the

SPKF is transferred to an experimental platform, demonstrating that the ROM and SPKF can run together on an inexpensive micro-controller and that accurate electrochemical-state estimates can be achieved with the PBM reduction techniques. The results reported in this paper bring the opportunity to develop further battery-control systems using physics-based performance limits. Overall, this work: (1) improves the operating range of the ROMs by introducing an output-blending technique that gives better predictions than the prior model-blending technique; (2) shows how to apply an SPKF to the output-blended ROMs to estimate cell internal electrochemical variables as well as terminal voltage; (3) demonstrates the accuracy of the combined output-blended ROM and SPKF both in simulation and experimentally; and (4) shows that ROMs are suitable for implementation in a practical BMS using inexpensive micro-controllers.

This paper is organized as follows: Sect. II introduces the ROM that we use in this work; Sect. III summarizes the SPKF; Sect. IV presents both simulation and real-world results produced by the method; and Sect. V makes some concluding remarks.

II. ELECTROCHEMICAL MODEL IMPLEMENTATION

This section describes the ROM implementation. A discrete-time state-space model is created using a model-order-reduction process in order to lower the electrochemical model's computational complexity to prepare it for use on a practical BMS that does not require powerful computational resources.

A. FULL-ORDER MODEL

The ROM to be presented is based on the widely known “pseudo two-dimensional” (P2D) FOM first proposed by Doyle *et al.* [26], [27]. This FOM is able to predict a cell's internal electrochemical states by solving a group of four partial-differential equations (PDEs) coupled by an algebraic closure term. These equations are summarized below (for brevity, we omit a discussion of the boundary conditions for these equations, but a full derivation, including boundary conditions, can be found in [28]).

Solid-phase charge conservation

The PDE describing charge conservation in the solid electrode particle matrix is

$$\frac{\partial}{\partial x} \left(\sigma_{\text{eff}} \frac{\partial \phi_s}{\partial x} \right) = a_s F j \quad (1)$$

where ϕ_s is the potential in the electrode solid active material as a function of position and time, σ_{eff} is the effective solid electronic conductivity, a_s is the specific interfacial surface area, j is the flux of lithium moving from the solid to the electrolyte as a function of position and time, and F is Faraday's constant.

Solid-phase mass conservation

The PDE describing mass conservation in the solid is

$$\frac{\partial c_s}{\partial t} = \frac{1}{r^2} \frac{\partial}{\partial r} \left(D_s r^2 \frac{\partial c_s}{\partial r} \right) \quad (2)$$

where c_s is the concentration of lithium in the electrode solid active material as a function of position and time and D_s is the solid diffusivity.

Electrolyte-phase mass conservation model reformulation

The PDE describing of mass conservation in the electrolyte is

$$\frac{\partial (\varepsilon_e c_e)}{\partial t} = \frac{\partial}{\partial x} D_{e,\text{eff}} \frac{\partial c_e}{\partial x} + a_s (1 - t_+^0) j \quad (3)$$

where c_e is the concentration of lithium in the electrolyte as a function of position and time, ε_e is the electrolyte volume fraction, and $D_{e,\text{eff}}$ is the effective electrolyte diffusivity.

Electrolyte-phase charge conservation

The PDE describing charge conservation in the electrolyte is

$$-a_s F j = \frac{\partial}{\partial x} \kappa_{\text{eff}} \frac{\partial \phi_e}{\partial x} + \frac{2RT(t_+^0 - 1)}{F} \left(1 + \frac{\partial \ln f_{\pm}}{\partial \ln c_e} \right) \frac{\partial}{\partial x} \kappa_{\text{eff}} \frac{\partial \ln c_e}{\partial x}$$

where ϕ_e is the potential in the electrolyte as a function of position and time, κ_{eff} is the effective electrolyte ionic conductivity, R is the universal gas constant, T is absolute temperature, t_+^0 is the transference number of the cation with respect to the solvent in the electrolyte, and f_{\pm} is the mean molar activity coefficient of the electrolyte.

Reaction kinetics model reformulation

The Butler–Volmer equation describing reaction kinetics is

$$j = k_0^{\text{norm}} \left(\frac{c_e}{c_{e,0}} \right)^{1-\alpha} \left(1 - \frac{c_{s,e}}{c_{s,\text{max}}} \right)^{1-\alpha} \left(\frac{c_{s,e}}{c_{s,\text{max}}} \right)^{\alpha} \times \left(\exp \left(\frac{(1-\alpha)F}{RT} \eta \right) - \exp \left(\frac{-\alpha F}{RT} \eta \right) \right) \\ \eta = \phi_s - \phi_e - U_{\text{ocp}}(c_{s,e}/c_{s,\text{max}}) - F R_f j,$$

where k_0^{norm} is the reaction-rate constant, $c_{s,\text{max}}$ is the maximum lithium concentration in the solid, α is the charge-transfer coefficient, U_{ocp} is the open circuit potential of the solid material as a function of its argument, and R_f is the solid–electrolyte interphase film resistivity.

B. REDUCED-ORDER MODEL

The FOM just summarized can be linearized around specific constant-SOC and constant-temperature setpoints and converted to a frequency-domain transfer-function representation [20], [24], [28]. These transfer functions can then be converted to a discrete-time ROM using subspace-projection techniques [21], [25], [28]. The linearizing process replaces FOM variables ϕ_s , ϕ_e , c_s , and c_e with debiased versions: $\check{\phi}_s$, $\check{\phi}_e$, \check{c}_s , and \check{c}_e , respectively. The ROM directly produces

predictions of $\tilde{\phi}_s$, $\tilde{\phi}_e$, \tilde{c}_s , \tilde{c}_e , and j ; we must apply nonlinear corrections to these predictions to produce predictions of the original variables ϕ_s , ϕ_e , c_s , c_e , and cell voltage (these corrections are described further in Sect. II-C3). The structure of the ROM is a linear discrete-time state-space model of the form

$$x[k+1] = Ax[k] + Bu[k] \quad (4)$$

$$y[k] = Cx[k] + Du[k], \quad (5)$$

where $x[k]$ is a semi-physical state vector (having dimension n) at discrete-time index k , $u[k]$ is the input, which in this case is the applied cell current, $y[k]$ is the set of linear model outputs (which must be corrected) and $\{A, B, C, D\}$ are the matrices required to describe the dynamics of the cell, generated by the DRA from the cell's physical parameters.

Any ROM created in this way is able to make accurate predictions of the original electrochemical variables when the cell is operated close to the specific constant-SOC and constant-temperature setpoint used to generate the ROM. In order to generalize the ROM to a wide SOC and temperature operating range, we must somehow combine the effect of individual ROMs created at different setpoints. Two candidate blending methods are described in Sect. II-C.

The final ROM can be implemented in a variety of programming languages and environments. Here, we first prototype the methods in MATLAB/Simulink. The algorithm itself is mainly developed in MATLAB code so that it finally can be inserted in Simulink as a "MATLAB function block". The reason for this type of hybrid implementation is to combine the ease of operating with matrices in MATLAB code and the signal management of Simulink.

The structure of the whole implementation is shown in Fig. 1. The "Initial State" of the battery cell, the applied "Input Current", and ambient "Input Temperature" are the model's inputs and the internal cell electrochemical variables and predicted terminal voltage are the outputs.

Looking deeper into the model, three differentiated parts can be identified. The first is the "Augmented state-space Model" that will be described in Sect. II-C1. The second corresponds to the main "Model Simulation" loop in which the state-space vector and the linear outputs of the model are calculated. Finally, the third part applies "Nonlinear Corrections" to the output to improve predictions and to overcome model inaccuracies introduced in the linearization step of the model-order-reduction process.

C. BLENDING DIFFERENT ROMS

A key component to make the overall ROM viable for a practical implementation is that we must somehow be able to combine individual ROMs generated at different SOC and temperature setpoints to make predictions that are valid over the entire operational range. The first approach presented here blends models at every point in time to create a single time-varying model that is updated every timestep; this method is called "model blending" [29]. The second

approach keeps individual models distinct and updates all models at every timestep; it then blends outputs from each model together to cause the overall output to represent a time-varying dynamic; this method is called "output blending" [30]. We review both of these approaches here.

1) Model blending

The model-blending approach begins with the general state-space form of Eqs. (4) and (5). For computational simplicity, the model is normalized by the DRA (without loss of generality) such that the A matrix is diagonal with positive elements, and the B matrix is a units vector having the same dimensions as $x[k]$ (i.e., $B = 1_{n \times 1}$). The model is organized so that the elements on the diagonal of the A matrix are in increasing order, and since the model will always be (marginally) stable and have an integration state, the largest element in the A matrix corresponds to the integration dynamics and has value "1".

In a BMS application, the model's state predictions are corrected with a SPKF, as will be explained in Sect. III. The SPKF is a nonlinear generalization of the standard Kalman filter and is designed to modify the state-vector estimate of a model in real time so that the model's output predictions match the physical reference measurements more closely. At any point in time, the SPKF requires a single state-space model describing the battery cell's dynamics at that point in time. However, this is a problem because we find that a single state-space model produced by the DRA is not adequate to predict a cell's dynamics over a wide range of SOC and temperature, as is required in a practical BMS application.

In prior works, a method called "model blending" was used to overcome this limitation [29], [31], [32]. Equations (4) and (5) are modified to use time-varying $\{A, B, C, D\}$ matrices:

$$x[k+1] = A[k]x[k] + B[k]u[k] \quad (6)$$

$$y[k] = C[k]x[k] + D[k]u[k]. \quad (7)$$

First, the DRA is used to precompute static $\{A, B, C, D\}$ matrices corresponding to models linearized around a collection of individual setpoints on a grid of SOC and temperatures spanning the expected operational environment of the cell. Then, as the SPKF operates, the state-space matrices from the four precomputed models having closest setpoint to the present cell SOC and temperature are blended together at every point in time to create the time-varying state-space matrices corresponding to that specific point in time.

This is illustrated in Fig. 2 (left frame), applied to compute the model's time-varying "A" matrix. The cell's present state of charge is marked on the figure as "SOC", and SOC_0 and SOC_1 are the state-of-charge setpoints of the closest precomputed models to the present operational SOC that bracket the present SOC. Similarly, the cell's present temperature is marked on the figure as "T" and T_0 and T_1 are the temperature setpoints of the closest precomputed models to the present operational temperature that bracket the present




FIGURE 1. Scheme of the ROM model implementation.

temperature. So, SOC_0 and T_0 are both lower than or equal to the present SOC and temperature, SOC_1 and T_1 are both greater than or equal to the present SOC and temperature, and we have precomputed ROMs using the DRA at all combinations of T_0 , T_1 , SOC_0 , and SOC_1 . Once these four closest models are identified, the present time-varying $A[k]$ matrix is computed via bilinear interpolation of the constant A matrices of the closest models.

Specifically, if we define

$$\theta = \frac{SOC - SOC_0}{SOC_1 - SOC_0}$$

$$\psi = \frac{T - T_0}{T_1 - T_0},$$

then

$$A[k] = (1 - \psi)((1 - \theta)A_{0,0} + \theta A_{1,0}) + \psi((1 - \theta)A_{0,1} + \theta A_{1,1})$$

$$= \gamma_{0,0}A_{0,0} + \gamma_{0,1}A_{0,1} + \gamma_{1,0}A_{1,0} + \gamma_{1,1}A_{1,1}.$$

The same bilinear-interpolation process is applied to find time-varying $B[k]$, $C[k]$, and $D[k]$ matrices at every timestep:

$$B[k] = \gamma_{0,0}B_{0,0} + \gamma_{0,1}B_{0,1} + \gamma_{1,0}B_{1,0} + \gamma_{1,1}B_{1,1}$$

$$C[k] = \gamma_{0,0}C_{0,0} + \gamma_{0,1}C_{0,1} + \gamma_{1,0}C_{1,0} + \gamma_{1,1}C_{1,1}$$

$$D[k] = \gamma_{0,0}D_{0,0} + \gamma_{0,1}D_{0,1} + \gamma_{1,0}D_{1,0} + \gamma_{1,1}D_{1,1}.$$

The SPKF uses the time-varying model of Eqs. (6) and (7) to produce predictions of the model state and from that the model internal electrochemical variables [31].

The model-blending method requires knowledge of the present temperature and cell SOC. In practice, the temperature is known by measurement, but the SOC must be estimated. The cell's initial SOC can be estimated using a known open-circuit-voltage (OCV) versus SOC relationship (assuming that the cell is initially at rest). Subsequently, the time-varying SOC estimate is produced as an output of the SPKF, and the previous cell SOC estimate is used as input to the bilinear interpolation process for use in computing the present cell state estimate.

2) Output blending

Model blending makes an implicit assumption that is not true in general, and so predictions of electrochemical variables and cell voltage made using model blending are not always accurate. This incorrect assumption is that the state vectors in the individual models that are being blended together all have the same physical interpretation, and therefore that the $\{A, B, C, D\}$ matrices can be blended directly to approximate the actual time-varying linearized model. However, each precomputed model is found as the output of a numerical linear-algebra procedure as one step of the DRA known as the ‘‘Ho–Kalman’’ method, and this method does not guarantee that all models will have state vectors with a known or consistent physical interpretation. Therefore, we no longer recommend that model blending be used.

Instead, we propose that ‘‘output blending’’ be used [30]. Precomputed models produced by the DRA or other realization algorithms like the continuous-time realization algorithm (CRA), hybrid realization algorithm (HRA), or Lagrange-interpolated realization algorithm (LRA) [25], [30] do not guarantee physical meaning of the state vector $x[k]$ but they do guarantee physical meaning of the linearized output vector $y[k]$. Therefore, while it is not appropriate to blend states directly together as is effectively done by model blending, it is appropriate to blend together model outputs.

‘‘Output blending’’ still maintains the concept of interpolating the influence of four neighboring models. The implementation is however completely different. First, model blending works with a single time-varying model and therefore needs to update only one state vector $x[k]$ at every point in time. Output blending, however, must update the state vector for every precomputed model at every point in time. That is, it computes

$$x_j[k + 1] = A_j x_j[k] + B_j u[k],$$

for all $1 \leq j \leq N$, where $x_j[k]$ is the state of model j , A_j and B_j are the constant state-equation matrices for precomputed model j , and N is the number of precomputed models. Updating every model's state requires more computation than




FIGURE 2. Bilinear interpolation of the $A[k]$ matrix for “model blending” (left) and bilinear interpolation of the model output $y[k]$ for “output blending” (right)..

the equivalent operation for model blending, but the overhead can be minimized by using diagonal A_j matrices and units B_j matrices, as already described. Also, since all models will have identical integral states, the integration can (and should, when using SPKF) be factored out of all models and computed separately. For example, if $x_j[k]$ for each model is a 5×1 vector, then we remove the integration state, retaining only the transient states, and $x_j[k]$ becomes a 4×1 vector, which we rename $x'_j[k]$. Similarly, the 5×5 A_j matrix becomes a 4×4 (diagonal) matrix renamed A'_j and the 5×1 B_j vector becomes a 4×1 vector renamed B'_j :

$$x'_j[k + 1] = A'_j x'_j[k] + B'_j u[k].$$

The single integral state $x_0[k]$ common to all models is updated as

$$x_0[k + 1] = x_0[k] + u[k].$$

Taken altogether, this is the same as

$$\underbrace{\begin{bmatrix} x'_1[k + 1] \\ \vdots \\ x'_N[k + 1] \\ x_0[k + 1] \end{bmatrix}}_{x[k+1]} = \underbrace{\begin{bmatrix} A'_1 & & 0 \\ & \ddots & \\ 0 & & A'_N \\ & & & 1 \end{bmatrix}}_{A'} \underbrace{\begin{bmatrix} x'_1[k] \\ \vdots \\ x'_N[k] \\ x_0[k] \end{bmatrix}}_{x[k]} + \underbrace{\begin{bmatrix} B'_1 \\ \vdots \\ B'_N \\ 1 \end{bmatrix}}_{B'} u[k], \quad (8)$$

where we have redefined $x[k]$ to include all the states of all the precomputed models. This new $x[k]$ has dimension $(N(n - 1) + 1) \times 1$.

Next, output blending uses bilinear interpolation to combine the outputs of the models corresponding to the four set-points closest to the present operating SOC and temperature.

This is illustrated in Fig. 2(right frame). As before, if we define

$$\theta = \frac{SOC - SOC_0}{SOC_1 - SOC_0}$$

$$\psi = \frac{T - T_0}{T_1 - T_0}.$$

Then,

$$y[k] = (1 - \psi)((1 - \theta)y_{0,0}[k] + \theta y_{1,0}[k]) + \psi((1 - \theta)y_{0,1}[k] + \theta y_{1,1}[k]) \quad (9)$$

$$= \gamma_{0,0}y_{0,0}[k] + \gamma_{0,1}y_{0,1}[k] + \gamma_{1,0}y_{1,0}[k] + \gamma_{1,1}y_{1,1}[k] \quad (10)$$

$$= \sum_{j=1}^N \gamma_j y_j[k]. \quad (11)$$

Notice that although we must update the state vector of all models every time step, we are not required to compute the output vector of any model that is not being used for the present calculation of $y[k]$. That is, in the set of weighting constants $\{\gamma_j\}$ for $1 \leq j \leq N$ in Eq. (11), only the four closest models have nonzero weights, denoted as $\gamma_{0,0}$, $\gamma_{0,1}$, $\gamma_{1,0}$, and $\gamma_{1,1}$ in Eq. (10). This reduces the required computation.

The outputs required by Eq. (9) could be computed using the full-sized state vectors as

$$y_j[k] = C_j x_j[k] + D_j u[k].$$

We can also use the integrator-removed state vectors if we define C'_j to be the first $n - 1$ columns of C_j and C_0 to be the final column of C_j (this column comprises the “residues” of the integration state and is not a function of SOC or temperature and so is identical for all precomputed models). Then,

$$y_j[k] = [C'_j \quad C_0] \begin{bmatrix} x'_j[k] \\ x_0[k] \end{bmatrix} + D_j u[k].$$

The output-blended final result is then

$$y[k] = C_0 x_0[k] + \sum_{j=1}^N \gamma_j (C'_j x_j[k] + D_j u[k]). \quad (12)$$

The summation is written for $1 \leq j \leq N$ but since only four values of γ_j are nonzero, computation is reduced by considering only the nonzero terms in the summation.

3) Outputs and Nonlinear Corrections

A ROM generated using the DRA is capable of computing predictions for a very general set of outputs that might be desired by the user, including the concentration of lithium in the electrolyte (c_e), the solid surface concentration ($c_{s,e}$), the Butler–Volmer reaction flux (j) and reaction overpotential (η), the electric potential in the electrolyte (ϕ_e), the electric potential in the solid (ϕ_s), and the solid–electrolyte potential difference (ϕ_{s-e}). Any or all of these variables can be predicted at any desired sets of internal spatial locations along the 1-d cross section of the cell. Furthermore, cell voltage (v) may also be predicted.

During the derivation of the ROM, the nonlinear components of the FOM equations are isolated and constant biases are subtracted to produce the linear state-space model that has been described to this point. Consequently, the linear outputs of the state-space ROM now need to be corrected in order to model the nonlinearity of the real battery cell. In [28] and [20] the linearized variables are noted with the tilde (“~”) symbol so the same notation will be adopted through this document. These corrections need to be applied to the cell voltage v_{cell} , concentration in the electrolyte c_e , solid surface concentration $c_{s,e}$, potential of electrolyte ϕ_e and solid-electrolyte Potential difference ϕ_{s-e} . A detailed description of these corrections can be found in [28].

III. SIGMA-POINT KALMAN FILTER

So far, we have introduced a reduced-order model able to predict the internal variables of a cell in addition to its voltage. This model is compact in terms of memory size and computational requirements, and is thus well-suited for implementation in a micro-controller. We might consider using this ROM directly in a BMS to aid with computation of cell SOC, SOH, available energy and power and so forth. However, use in a real-world application introduces some complicating factors that must be overcome before the ROM predictions are considered accurate and meaningful. In particular, we must recognize that the models have been designed with imperfect assumptions and that we must consider some features of the overall battery system in which the cell operates.

- **Every single battery cell is different:**

All battery cells—even from the same brand or the same model—are slightly different. The manufacturing processes are never perfect and therefore inhomogeneities related to the materials and assembly appear in the final product. This could be considered as a minor effect

but if, for example, the initial total-capacity dispersion between cells is considered, it can be shown that meaningful differences appear in predictions of voltage and internal electrochemical variables versus true-cell behaviors. The model created for a specific sample cell (the one used for the parametrization of the model) will not generally be as accurate for other very similar cells. Therefore the errors in the predictions of internal variables produced by this model can in some cases be significant, and consequently inhomogeneities cannot always be considered negligible.

- **The electrical current applied to the cell and its internal temperature cannot be perfectly measured:** The cell’s applied current and its core temperature are the inputs of the model. In a simulation scenario, these data are introduced to the model in a straightforward manner. When thinking about a real-case scenario, on the contrary, measurement noise on the current sensor introduces error; cell internal temperature cannot be measured directly, and externally measured temperatures also contain measurement error.
- **The reduced order model is not a perfect description of cell dynamics:**

The ROM that we use is a highly accurate approximation to the FOM, but nonetheless it is an approximation. Errors are introduced by the model-order reduction process, the discrete-time nature of the ROM, and the fact that we generate ROMs only at specific operational setpoints (this latter factor is mitigated by blending the outputs of nearby models). Additionally, the FOM itself has intrinsic error due assumptions made when deriving its equations, especially homogenizing parameter values and dynamics over multiple scales.

All these facts make it necessary somehow to create a solution that reduces the amount of error introduced in the predictions by these factors to make the predictions computed by the enhanced system valid for any cell (cells that are the same model of a certain brand). Kalman filters are a technology that when added to the ROMs in this case produce a logical solution to this problem.

Kalman filters are based on a framework named “sequential probabilistic inference” [33]. Using a model of the system being described and a feedback of the real response of that system, the filters adjust the internal states of the model to make the predictions converge to better results. In the specific case of a battery cell, the most evident response of the system is the output voltage which is used as a feedback. It is worth mentioning at this point that measurement noise on the voltage sensor will also introduce error via the feedback mechanism of the Kalman filter; nevertheless, this error (as well as the other error sources itemized above) is taken into account when the filter is developed in order to optimize its estimates. However, because of measurement noises and modeling errors, it is not possible to make perfect state estimates. Therefore, very importantly, the Kalman filter uses

probability theory to compute confidence bounds on its estimates. This means that the filter will give accurate estimates as well as confidence bounds within which the true value of the variable being estimated is expected to be contained. The theory behind “sequential probabilistic inference” and Kalman filters requires a lengthy explanation to derive and is out of the scope of this article, nevertheless a detailed explanation, including application to battery state estimation using equivalent-circuit models, can be found in [33].

Different varieties of Kalman filter can be found in the literature. The original linear Kalman filter, for example, is a very well-known and commonly used approach demonstrated to produce very good estimates when applied to linear systems (provably optimal estimates if the assumptions made in the derivation hold). The extended Kalman filter (EKF, the most popular form of nonlinear Kalman filter) and the sigma-point Kalman filter (SPKF, which includes the “unscented Kalman filter” or UKF as a subcategory) are suboptimal generalizations of the linear Kalman filter specifically designed to be applied to nonlinear systems. A thorough study of these filters applied to the state-space ROM utilized in this paper (but using model blending instead of output blending) was carried out by [31]; results for EKF were also reported in [32]. The main conclusion of this work was that due to the nonlinear dynamics of lithium-ion battery cells, a nonlinear filter is required. Both EKF and SPKF could be tuned to give good performance. In addition to this the SPKF has several advantages when comparing it with EKF. These differences are explained below, and a more detailed discussion can be found in [33].

- Derivatives do not need to be computed
- No need for differentiable functions
- Better covariance approximations
- Comparable computational complexity

A. SIGMA-POINT KALMAN FILTER IMPLEMENTATION

All Kalman filters are based on the “sequential probabilistic inference” solution, and consequently share its underlying six-step process (two major steps, each having three sub-steps). Every measurement interval, there are three prediction sub-steps and another three sub-steps that correct those predictions to produce a state estimate along with its confidence bounds. In the following, the six steps will be briefly explained (more detailed information can be found in [31], [33]).

Before explaining the six-step process, it is necessary to define the model that will be considered in the Kalman filter. The nonlinear state space model created in Sect. II-C1 will be used with the following notation.

$$x[k] = f(x[k-1], u[k-1] + w[k-1]) \quad (13)$$

$$v_{cell}[k] = h(x[k], u[k]) + v[k]. \quad (14)$$

Equations (13) and (14) represent the state equation and output-measurement equation, respectively, of the model used by the SPKF. This means that $f(\cdot)$ is related to Eq. (8)

and $h(\cdot)$ to Eq. (??), where the variables required to compute voltage are computed via Eq. (12). The difference is that Eq. (13) contains a new “process-noise” term $w[k]$ and Eq. (14) contains a new “measurement-noise” term $v[k]$. The process noise is assumed to be white additive Gaussian measurement noise on the current sensor, added directly to $u[k]$. The measurement noise is assumed to be white additive Gaussian noise added directly to the true voltage.

The application of the SPKF to Eqs. (13) and (14) will now be described. The fact that Eq. (13) is linear for the ROM we are using results in some computational simplifications to the implementation versus the standard SPKF method.

- **Step 1a:** State prediction time update.

The first step of the SPKF, every iteration, is to predict the present value of the state using only prior information. We define $\hat{x}^- [k] = \mathbb{E}[x[k] | v_{cell}[0] \dots v_{cell}[k-1]]$ where we continue to consider $x[k]$ to be the collection of all states of all precomputed models at time k . That is, we consider

$$x[k] = \begin{bmatrix} x'_1[k] \\ \vdots \\ x'_N[k] \\ x_0[k] \end{bmatrix}. \quad (15)$$

Therefore, using Eq. (8), we conclude that

$$\hat{x}^- [k] = A' \hat{x}^+ [k-1] + B' u[k-1],$$

where $\hat{x}^+ [k-1]$ is the state estimate produced by the SPKF for the prior iteration.¹

- **Step 1b:** State prediction-error covariance update.

The next step of the SPKF, every iteration, is to compute the covariance (uncertainty) of the state prediction. We define

$$\Sigma_{\hat{x}}^- [k] = \mathbb{E}[(x[k] - \hat{x}^- [k])(x[k] - \hat{x}^- [k])^T],$$

which leads to

$$\Sigma_{\hat{x}}^- [k] = (A')^T \Sigma_{\hat{x}}^+ [k-1] A' + (B')^T \Sigma_{\bar{w}} B',$$

where $\Sigma_{\hat{x}}^+ [k-1]$ is the covariance (uncertainty) matrix of the state estimate produced by the SPKF for the prior iteration and $\Sigma_{\bar{w}}$ is the covariance of the current-sensor measurement noise.

- **Step 1c:** Output prediction.

The third sub-step of the SPKF every iteration is to predict the voltage measurement. Since nonlinear Eq. (??) must be used, we must turn to the sigma-point approach to approximating the mean and uncertainty of a random variable computed using a nonlinear equation.

The mean and error-covariance of the state prediction are used to form a set of sigma points

$$\mathcal{X}^- [k] = \left\{ \hat{x}^- [k], \hat{x}^- [k] + h \sqrt{\Sigma_{\hat{x}}^-}, \hat{x}^- [k] - h \sqrt{\Sigma_{\hat{x}}^-} \right\}, \quad (16)$$

¹Noticing that A' is diagonal and that B' is a vector of units values can greatly simplify the computational complexity of an implementation in many of the SPKF steps.

where h is a tuning variable for the SPKF (often chosen as $h = \sqrt{3}$), $\sqrt{(\cdot)}$ is the lower-triangular matrix square root of its argument (usually computed using a Cholesky decomposition), and the somewhat nonstandard notation of Eq. (16) indicates that the zeroth member of set \mathcal{X}^- is the vector $\hat{x}^-[k]$, the next member of the set is $\hat{x}^-[k]$ plus h times the first column of $\sqrt{\Sigma_{\bar{x}}^-}$, the next member is $\hat{x}^-[k]$ plus h times the second column of $\sqrt{\Sigma_{\bar{x}}^-}$, and so forth.²

For each element $\mathcal{X}_i^-[k]$ in $\mathcal{X}^-[k]$, we compute the linear model outputs using Eq. (12). Then, we apply nonlinear corrections to produce a voltage prediction based on that element. That is, overall we find nonlinear-output sigma points:

$$\mathcal{V}_i[k] = h(\mathcal{X}_i^-[k], u[k]).$$

The weighted mean of these points is the voltage prediction we are seeking to compute:

$$\hat{v}_{cell}[k] = \sum_{i=0}^{8n-6} \alpha_i^{(m)} \mathcal{V}_i[k],$$

where $\alpha_i^{(m)}$ are tuning variables for the SPKF when computing this mean value.

• **Step 2a:** Estimator gain matrix.

We have now predicted the present state and present measurement, and have computed the covariance of the state-prediction error using only prior information. The next steps update the prediction using present information to compute the state estimate and its uncertainty. A key feature is the computation of a time-varying estimator gain matrix $L[k]$.

We begin by computing the covariance of the voltage-prediction error

$$\Sigma_{\bar{v}}[k] = \sum_{i=0}^{8n-6} \alpha_i^{(c)} (\hat{v}_{cell}[k] - \mathcal{V}_i[k]) (\hat{v}_{cell}[k] - \mathcal{V}_i[k])^T + \Sigma_{\bar{v}}, \quad (17)$$

where $\alpha_i^{(c)}$ are tuning variables for the SPKF when computing covariances. We also compute the cross covariance between the state-prediction error and the voltage-prediction error:

$$\Sigma_{\bar{x}\bar{v}}[k] = \sum_{i=0}^{8n-6} \alpha_i^{(c)} (\hat{x}^-[k] - \mathcal{X}_i^-[k]) (\hat{v}_{cell}[k] - \mathcal{V}_i[k])^T. \quad (18)$$

²As written in Eq. (16), the total number of elements in \mathcal{X}^- is $1 + 2(N(n-1) + 1)$ where we recognize that the dimension of $\hat{x}^-[k]$ is $N(n-1) + 1$. However, recognizing that only a subset of four of the N models is used when computing outputs using output blending, we can compute a reduced version comprising only the relevant $1 + 2(4(n-1) + 1) = 8n - 5$ elements, indexed from 0 to $8n - 6$.

After these are computed, the state-estimator gain matrix can be found as³

$$L[k] = \Sigma_{\bar{x}\bar{v}}[k] (\Sigma_{\bar{v}}[k])^{-1}. \quad (19)$$

• **Step 2b:** State estimate measurement update.

The state prediction is now updated using the measured value of voltage to become a state estimate⁴

$$\hat{x}^+[k] = \hat{x}^-[k] + L[k] (v_{cell}[k] - \hat{v}_{cell}[k]). \quad (20)$$

• **Step 2c:** State estimation-error covariance.

To complete the process, the estimation-error covariance matrix is updated so all the necessary values for the next iteration are computed:⁵

$$\Sigma_{\bar{x}}^+[k] = \Sigma_{\bar{x}}^-[k] - L[k] \Sigma_{\bar{v}}[k] L^T[k]. \quad (21)$$

At this point, we have updated the state estimate and its covariance (uncertainty) matrix. In many cases, we would also like to compute estimates of the cell's electrochemical internal variables and their uncertainties. In this case, we add an additional major step having two sub-steps

• **Step 3a:** Internal-variables estimate.

The cell's internal variables are nonlinear functions of the state, so once again, we must use the sigma-point method to find estimates of the internal variables and their estimation-error covariances. To estimate the internal variables, we will compute new sigma points based on the present state estimate and uncertainty:⁶

$$\mathcal{X}^+[k] = \left\{ \hat{x}^+[k], \hat{x}^+[k] + h\sqrt{\Sigma_{\bar{x}}^+}, \hat{x}^+[k] - h\sqrt{\Sigma_{\bar{x}}^+} \right\}. \quad (22)$$

We then define a function $g(\cdot)$ that converts the system state to the particular electrochemical variable of interest, which we denote as $z[k]$. Then, for each of the sigma points in the set $\mathcal{X}^+[k]$, we produce an output sigma point

$$\mathcal{Z}_i[k] = g(\mathcal{X}^+[k], u[k]).$$

Finally, we compute the estimate of the variable of interest as

$$\hat{z}^+[k] = \sum_{i=0}^{8n-6} \alpha_i^{(m)} \mathcal{Z}_i[k].$$

³Note that $\Sigma_{\bar{v}}[k]$ is a scalar since voltage is a scalar. Using the definition of $x[k]$ in Eq. (15), $\Sigma_{\bar{x}\bar{v}}^-$ has dimension $(N(n-1) + 1) \times 1$. However, since only four precomputed models contribute to the estimate $\hat{y}[k]$, the state-estimate of only four models will ultimately be updated in Step 2b. Therefore, we simplify computation by deleting the unnecessary components from $\Sigma_{\bar{x}\bar{v}}^-$ such that $\Sigma_{\bar{x}\bar{v}}^-$ ends up having dimension $(4(n-1) + 1) \times 1$ or $(4n-3) \times 1$. Similarly, $L[k]$ in Eq. (19) has condensed size $(4n-3) \times 1$.

⁴Using the condensed $L[k]$ vector from Step 2a, we must be careful to distribute the state-estimate updates only to the portion of the overall state estimate $\hat{x}^+[k]$ corresponding to four precomputed models that contributed in producing $\hat{y}[k]$.

⁵Using the condensed $L[k]$ vector from Step 2a, we must be careful to distribute the covariance updates only to the portion of the overall covariance matrix $\Sigma_{\bar{x}}^+[k]$ corresponding to the states of the four precomputed models that contributed in producing $\hat{y}[k]$.

⁶Once again, recognizing that only a subset of four of the N models is used when computing outputs using output blending, we can compute a reduced version of the set of sigma points for $\mathcal{X}^+[k]$ comprising only the relevant $1 + 2(4(n-1) + 1) = 8n - 5$ elements, indexed from 0 to $8n - 6$.

- **Step 3b:** Estimation-error covariance for internal variables.

Finally, we compute the covariance of the internal variable (useful for computing confidence intervals of the estimate) as

$$\Sigma_z^+[k] = \sum_{i=0}^{8n-6} \alpha_i^{(c)} (\hat{z}^+[k] - Z_i^+[k])(\hat{z}^+[k] - Z_i^+[k])^T.$$

At the output of this process, we have high confidence that the true variable is in the range $\hat{z}^+[k] \pm 3\sqrt{\Sigma_z^+[k]}$.

The overall process is illustrated in Fig. 3. It is worth mentioning at this point that during the design of the SPKF some assumptions have been made. First, in the definition of the filter, the process and sensor noises have been assumed to be uncorrelated. This is not true since the current sensor noise is considered to be process noise and current is an input to both state and output equations. Second, the temperature is measured and introduced in the model as an input. Nevertheless this value is measured but no error is considered. Even though these assumptions are known to be imperfect, the results are shown to be in very good agreement with reality (both using experimental and virtual data) as will be demonstrated in Sect. IV and Sect. IV-D. It is possible that future research will allow removing these assumptions and lead to even better results.

B. SIGMA POINT KALMAN FILTER INITIALIZATION

The initialization of Kalman filters before beginning the main program loop is a nontrivial and key step. The initial values of the state estimate ($\hat{x}^+[0]$) and its estimation-error covariance ($\Sigma_x^+[0]$) have significant influence on the early estimates produced by the filter. Further, it is conceivable that a very bad initialization might cause the filter to “get lost” and never converge to the neighborhood of the true state. Additionally, values for the process-noise and sensor-noise covariance matrices need to be specified. This topic is considered to be out of the scope of this article and the values used to produce the results of this paper were obtained based on an iterative trial-and-error process and on [31].

The model used to produce the results of this paper comprised four individual ROMs, linearized around the setpoint (SOC: from 0% to 100% in steps of 5%; Temperature: 20°C, 30°C for ambient temperature operation and 0°C, -10°C for cold-temperature operation). Each of these individual ROMs had $n = 5$ states. All states are initialized to 0; the covariance matrix is initialized to a diagonal matrix having a value of 10 in every diagonal element, except for the element corresponding to the integration state which had a value of 10^6 . The process-noise covariance was chosen to be $\Sigma_w = 0.4$ and the sensor-noise covariance was chosen to be $\Sigma_v = 0.1$.

Notice that during operation of the SPKF, only four pre-computed models are used to predict cell voltage at any point in time, and so only those same four models are updated using the measured-voltage feedback in Steps 2b and 2c. However, all models are updated in Steps 1a and 1b. Since

Step 1b has the effect of increasing the uncertainty of the states of a model and Step 2c has the effect of decreasing the uncertainty of states of a model, many models will have their uncertainty increase over time without having measurements that will then decrease their uncertainty. Since the actual cell being monitored has a time-varying SOC and temperature, we expect that different sets of four precomputed models will contribute to the voltage prediction at different points in time. Any time that this set of models changes, we will begin to blend in the effect of a precomputed model that possibly has a large covariance (large uncertainty of its states) since that model has not been updated using Steps 2b and 2c for some time. That is, we might expect a singularity when either SOC and/or temperature change such that we blend together a different set of four precomputed models from the set we have been using most recently. In fact, however, we do not experience this singularity since both SOC and temperature change relatively slowly. When we start to blend in a new model, the γ value associated with that model (cf. Eq. (11)) is near zero, and so the large uncertainty of that model does not have significant impact on the voltage prediction.

IV. EXPERIMENTAL RESULTS AND VALIDATION

This section is dedicated to evaluating the voltage and internal-variables estimates made by the ROM combined with the SPKF. It is important to evaluate estimation errors in order to verify and quantify the accuracy of the overall methodology. Ideally, this entire validation would be conducted using a physical cell, comparing the SPKF’s estimates against measured values from that cell. However, it is not known how to measure all the required internal variables of a cell in situ during operation, and estimates of these variables is one of the main benefits of the proposed approach. So, instead, since this paper presents the first application of SPKF to a DRA-produced ROM using output blending, we first explore the estimation accuracy by comparing estimates to “true” values produced by a simulation of the FOM. The estimator uses the set of precomputed reduced-order battery models, together with “measurements” of temperature and terminal voltage as its only inputs. The method produces estimates of cell terminal voltage, and assessing the estimation accuracy of this variable alone can be a good indicator of the overall method, but it is not enough to prove accurate estimates of cell internal electrochemical variables due to the low impact that some of them have on the voltage response. Therefore, we also compare estimates of these internal variables to the “true” values produced by simulation of the FOM.

However, it is also important to know whether the method will operate on a physical cell. Therefore, we also present results of an implementation of the ROM with SPKF on a physical cell. In this case, we cannot compare the method’s estimate of internal variables since the true values are not available for comparison. We are able to present results comparing estimates of cell voltage and SOC to true values, however.




FIGURE 3. Scheme of SPKF and ROM model implementation.

Within this section, we first describe the simulation-based validation efforts. In these scenarios, “virtual data” from a FOM simulation implemented in COMSOL are used as “truth” to compare with estimates made by the ROM with and without the SPKF. These data are enough to validate the ROM itself since they isolate the intrinsic errors coming from the model from errors that may have been made when parameterizing the model for a physical cell. This approach is also a very close approximation to the ROM plus SPKF working scenario. Estimates of the internal variables (c_e , $c_{s,e}$, ϕ_{s-e} , j), voltage, and SOC values for the case where only the ROM is used open-loop and with the corrections of the SPKF are presented and compared to those computed using the FOM. Then, we describe the hardware-based validation efforts on a physical cell.

A. ELECTROCHEMICAL VARIABLES EVALUATION

Once the virtual data are accessible, a method to quantify the proposed method’s estimation error faithfully is needed. In this document, an analysis of errors that are normalized based on the variability of the FOM predictions is adopted. This normalization allows a more consistent view of the errors between different variables having different operating ranges, and the effect on latter steps such as capacity fade or SOF management. Maximum and minimum values of each internal cell variable are identified from a range of FOM simulations, so a direct image of the maximum variability of each estimate is obtained. This variability is then used as a normalization factor, as described below.

Two types of profiles are used to evaluate the maximum variability of the battery variables: (1) constant-current charge and discharges at different C-rates, and (2) high-current pulses (C/5, C/4, C/3, 1C, 2C, 3C, 4C, and 5C for the constant-current charge and discharges plus 5C discharge and 1C charge for the current pulses as those are the current limits of the battery) at different SOC levels (1, 0.9, 0.8, 0.7, 0.6, 0.5, 0.4, 0.3, 0.2, and 0.1 SOC).

These profiles are selected in order to achieve the maximum and minimum values of the variables inside the cell. DC limit conditions are achieved with the full galvanostatic charge and discharges and maximum and minimum polarization effects are identified with the current pulses. According to the simulations performed, the variability measures that will be used for the error evaluation are shown in Table 1. These values will be used to normalize estimation errors such that the result is more easily understood. This normalization (error calculation) is carried out as shown in Eq. (23).

$$\text{Error (\%)} = \frac{(\theta_{ROM} - \theta_{FOM})}{\text{Variability}} \times 100. \quad (23)$$

B. MODEL EVALUATION WITHOUT AGING

We now evaluate the performance of the ROM predictions first without SPKF correction and then with SPKF-corrected estimates. In the first validation scenario, and for the sake of simplicity, a single charge and discharge cycle is used, without considering that the cell will age during its lifetime. Fig. 4(a) shows results for voltage and state of charge.

As stated before, while accurate voltage predictions are not sufficient to prove correctness of the method, when used together with estimates of SOC they help illustrate the model’s performance. During this charge and discharge cycle, the voltage error is kept under $\pm 0.1V$ and the SOC error under ± 0.05 in the worst case. Furthermore when using the SPKF, the SOC estimate is always within the SPKF-computed confidence interval, indicating a realistic state of charge estimate.

Figures 4(b)–(c) and 5(a)–(b) show the ROM (without SPKF) predictions and the ROM (with SPKF) estimates for c_e , $c_{s,e}$, ϕ_{s-e} and j in the negative electrode. All the ROM (without SPKF) predictions agree well with the true data with negligible error and ROM (with SPKF) estimates are similar. What it is more important is that the true data remains inside the confidence intervals produced by the SPKF.

TABLE 1. Variability of FOM electrochemical variables predictions.

Variables	Maximum	Minimum	Variability
c_e [mol m ⁻³]	2.7520×10^3	1.2534×10^3	1.4986×10^3
$c_{s,e}$ [mol m ⁻³]	2.0729×10^4	1.1075×10^3	1.9622×10^4
ϕ_{s-e} [V]	4.4058	-0.0329	4.4387
j [mol m ⁻² s ⁻¹]	4.1380×10^{-4}	-2.8386×10^{-4}	6.9765×10^{-4}




FIGURE 4. Cell voltage, SOC, c_e and $c_{s,e}$ ROM and SPKF predictions and prediction errors for a single charge and discharge cycle..

Taking a deeper look into the results, we can see occasional small peaks or jumps in the SPKF prediction error (this phenomena can be seen clearly in Fig. 4(b)). These peaks are attributed to changes to the set of four precomputed sub-models used to predict voltage, as explained in Sect. III-B.. This phenomenon appears when the SOC transitions to a different precomputed range (that is, where a submodel exists at a closer SOC point than one that is presently being used). When this happens one submodel is substituted and the corresponding covariance values are not necessarily precise. Further proof of the assumption that those peaks are produced by the submodel changes is that no peaks are observed when computing the ROM without the SPKF, implying that the perturbations are indeed introduced by the filtering. Despite the peaks, the SPKF tracks the variables correctly and recovers from those perturbations very quickly, updating the covariance values correctly. It has to be taken into account that a constant discharge profile is one of the most severe working scenarios for output blending, as the cell's SOC passes through all SOC ranges. The cause of the peaks could be addressed in future investigations in order to improve the system's overall response.

These results show a very good response for both the ROM without SPKF and the ROM with SPKF. Errors are kept very low and the true values remain within the estimator's confidence bounds (and, bounds do not exceed a 20% relative error for any variable). At this point it remains to validate the behavior of the ROM with SPKF with longer cycles to check its evolution in time as well as to evaluate performance when the cell ages.

Figure 5(c) shows the voltage and SOC responses during 20 cycles to check the evolution of the ROM with SPKF in time. Both voltage and SOC errors are greater when using the SPKF during the first one or two cycles, which is consistent with the results of the previous single-cycle analysis. Nevertheless, the SPKF starts to improve its estimates as time advances. Voltage error of the ROM without SPKF increases from the first time steps onward, while the estimates of the ROM with SPKF maintain a constant range of error. In the case of SOC, the error of the ROM without SPKF does not increase, while the error of the ROM with SPKF decreases from the first cycles onward. These results show the proper behavior of the ROM with SPKF and supports the validity of the method since the SPKF makes the ROM a more accurate tool. The tendency shown in Fig. 5(c) is maintained for the rest of the cell's internal variables, analogously, but we omit those results for brevity.

C. MODEL EVALUATION WITH AGING

The last step to validating the ROM with and without SPKF in simulation is to analyze the error evolution when the cell ages. When the battery starts to age, some internal-parameter values change (for example, see [34]). When using an aging model, parameters such as the stoichiometric range of electrode utilization can be predicted and directly corrected in the ROM. Nevertheless the volume fractions of

the electrolyte and anode (if we consider lithium plating and solid electrolyte interphase (SEI)-layer growth as the aging mechanisms occurring inside the cell) can not be varied in the ROM without recomputing individual ROMs from the revised parameter values for all linearization setpoints. This is because these parameter values introduced in the model equations are fixed during the linearization process and as this operation is precomputed offline and cannot be updated easily. This can be accommodated by precomputing ROMs over a wide aging window and using an advanced kind of SPKF [35], [36]. However, here we would like to investigate how variation of the electrolyte and negative-electrode volume fractions change the system predictions when the precomputed ROMs used by the SPKF are not updated as the cell ages.

TABLE 2. Aging parameters variation.

Variables	Maximum	Minimum	Variation
ϵ_s^{neg} [u/l]	0.357	0.311	12.88%
ϵ_e^{neg} [u/l]	0.471	0.411	12.73%

Volume fractions of the solid and electrolyte in the negative-electrode region (ϵ_s^{neg} and ϵ_e^{neg}) have been varied along a 40-cycle simulation of 1C charges and discharges. Table 2 shows that the initial and final values change approximately 13% over the simulation duration.

As shown in Fig. 6(a), the voltage and SOC prediction errors using the constant (new-cell) ROM without SPKF tend to increase as the cell ages and the time-varying FOM is consequently further away from the precomputed new-cell ROM. The estimates produced by the new-cell ROM with SPKF are better since the SPKF mitigates the error and keeps the true data inside the confidence bounds as the cell changes over time.

The predictions for c_e , $c_{s,e}$ and ϕ_{s-e} shown in Figs. 6(b)–(c) and 7(a), respectively, display a similar tendency. The results start with the same level of error as shown in the previous section, but the error increases over time.

Interestingly, Fig. 7(b) demonstrates that estimates of the flux along the negative electrode are not affected significantly as the cell ages. This gives consistency to the model as the flux is not expected to change dramatically as a function of volume fractions, and is instead more of a direct image of the applied current (which is not changed as the cycles are identical).

D. EXPERIMENTAL VALIDATION

For the experimental validation of the ROM and SPKF based system, a physical platform was implemented. This platform is composed of a DC-DC synchronous boost power converter, a Texas Instruments "TMS320F28379D" micro-controller (used to control the DC-DC converter, referred to as low-level control) and a Raspberry Pi 3 Model B+ micro-controller (used to implement the ROM and the SPKF system). The test battery cell is a SLPB 7.5 Ah high power NMC Kokam




FIGURE 5. ϕ_{s-e} and j ROM and SPKF predictions and prediction errors a). Cell voltage and SOC ROM and SPKF predictions and prediction errors during 20 cycles..

cell (SLPB75106100). Model parameters for the cell were

obtained in a previous research work [37].




FIGURE 6. Cell voltage, SOC, c_e and $c_{s,e}$ ROM and SPKF predictions and prediction errors for 40 cycles while aging..

The ROM and SPKF algorithm were implemented in the Raspberry Pi micro-controller to verify that the algorithm can run in an inexpensive microcontroller, as would be the case in a BMS. The algorithm receives battery cell temperature, voltage and current values (measured in the DC-DC converter

hardware and acquired by its control board, low-level control in Fig. 8) and executes the algorithm for each sampling interval (defined as 1s in this case, which we consider to be sufficiently fast to capture the dynamics of the cell under the applied load conditions).




FIGURE 7. ϕ_{s-e} and j ROM and SPKF predictions and prediction errors for 40 cycles while aging..




FIGURE 8. Validation platform general scheme. .

The battery cell was cycled at room temperature (22 °C approximately) and at -10 °C. The cell voltage prediction of the ROM with the SPKF was compared to the real cell voltage measurement in both cases. In Fig. 9, the voltage prediction and the measured voltage are shown for the cycles performed at both temperatures, as well as the SOC predic-

tion of the model.

Note that even when the ROM predictions differ from the true values, the SPKF adjusts the predictions to the experimental values of the cell at both temperatures. It is also important to note that the cell parameter identification was performed at positive reference temperatures. We believe




FIGURE 9. Experimental validation waveforms at room temperature (a) and at -10 °C (b).

this is why the ROM is less precise at $-10\text{ }^{\circ}\text{C}$, and as a consequence, the SPKF needs more time to adjust the prediction values to the measured data. However, it can be seen that after just a few cycles, the SPKF compensates and reduces the error of the prediction even at $-10\text{ }^{\circ}\text{C}$.

V. CONCLUSIONS

This paper presents computationally light physics-based reduced-order model able to predict the internal variables of a lithium-ion battery cell. The model utilizes “output blending” in order to improve accuracy over a wide range of ambient temperatures and operating SOC values. Further-

more, this paper has shown how to incorporate this model in a sigma-point Kalman filter to enable the use of measurement feedback to improve voltage and internal-variable estimates. Results demonstrate that the ROM without SPKF can produce good results, and that the ROM with SPKF can improve results even when the cell ages or extreme working conditions are considered and the model used by the SPKF is no longer perfectly accurate. Overall the presented system is able to predict accurately the behavior of a battery cell (including internal variables along the cross-sectional dimension, the cell voltage and the SOC) while being sufficiently lightweight computationally to implement

on a practical micro-controller. This system is therefore valid for battery-control dedicated online applications such as advanced BMS's seeking to control the battery based on electrochemical limits.

Finally the observed limitations of the work are gathered in this paragraph, together with the consequent future lines. First, even if the model accuracy is evaluated to be high overall, deviations can be observed at low working temperatures (see Fig. 9). This effect is attributed to a poor parameter identification at low temperatures, a topic that is still under research in the literature [37], and need for further investigation. In the system level an online oriented experimental setup has been implemented (see Fig. 8). Nevertheless, the proposed estimator should be validated in a commercial BMS hardware, integrated in an objective application. In that scenario, a real case evaluation of noises and computational load suitability can be done for the specific application under study. Finally, the model accuracy will decay while the cell ages, and consequently the states predictions will follow the same tendency (even if the SPKF will mitigate this effect). This is a key topic already contemplated in literature [3], [38], and future investigations will potentially advance towards a solution.

REFERENCES

- [1] Xiaosong Hu, Fei Feng, Kailong Liu, Lei Zhang, Jiale Xie, and Bo Liu. State estimation for advanced battery management: Key challenges and future trends. *Renewable and Sustainable Energy Reviews*, 114:109334, 2019.
- [2] Weihan Li, Damas W. Limoge, Jiawei Zhang, Dirk Uwe Sauer, and Anuradha M. Annaswamy. Estimation of potentials in lithium-ion batteries using machine learning models. *IEEE Transactions on Control Systems Technology*, pages 1–16, 2021.
- [3] Muratahan Aykol, Chirranjevi Balaji Gopal, Abraham Anapolsky, Patrick K. Herring, Buis van Vlijmen, Marc D. Berliner, Martin Z. Bazant, Richard D. Braatz, William C. Chueh, and Brian D. Storey. Perspective—combining physics and machine learning to predict battery lifetime. *Journal of The Electrochemical Society*, 168(3):030525, mar 2021.
- [4] Fei Feng, Sangli Teng, Kailong Liu, Jiale Xie, Yi Xie, Bo Liu, and Kexin Li. Co-estimation of lithium-ion battery state of charge and state of temperature based on a hybrid electrochemical-thermal-neural-network model. *Journal of Power Sources*, 455:227935, 2020.
- [5] K. Liu, Y. Shang, Q. Ouyang, and W. D. Widanage. A data-driven approach with uncertainty quantification for predicting future capacities and remaining useful life of lithium-ion battery. *IEEE Transactions on Industrial Electronics*, 68(4):3170–3180, 2021.
- [6] Kailong Liu, Xiaosong Hu, Huiyu Zhou, Lei Tong, Dhammika Widanage, and James Marco. Feature analyses and modelling of lithium-ion batteries manufacturing based on random forest classification. *IEEE/ASME Transactions on Mechatronics*, pages 1–1, 2021.
- [7] Ali Jokar, Barzin Rajabloo, Martin Désilets, and Marcel Lacroix. An Inverse Method for Estimating the Electrochemical Parameters of Lithium-Ion Batteries I. Methodology. *Journal of The Electrochemical Society*, 163(14):A2876–A2886, 2016.
- [8] Venkat R Subramanian, James A Ritter, and Ralph E White. Approximate solutions for galvanostatic discharge of spherical particles i. constant diffusion coefficient. *Journal of the Electrochemical Society*, 148(11):E444–E449, 2001.
- [9] Venkat R Subramanian, Vijayasekaran Boovaragavan, and Vinten D Diwakar. Toward real-time simulation of physics based lithium-ion battery models. *Electrochemical and Solid-State Letters*, 10(11):A255–A260, 2007.
- [10] Venkat R Subramanian, Vijayasekaran Boovaragavan, Venkatesailanathan Ramadesigan, and Mounika Arabandi. Mathematical model reformulation for lithium-ion battery simulations: Galvanostatic boundary conditions. *Journal of The Electrochemical Society*, 156(4):A260–A271, 2009.
- [11] Guodong Fan and Marcello Canova. Model order reduction of electrochemical batteries using galerkin method. In *ASME 2015 Dynamic Systems and Control Conference*, pages V001T13A006–V001T13A006. American Society of Mechanical Engineers, 2015.
- [12] Domenico Di Domenico, Giovanni Fiengo, and Anna Stefanopoulou. Lithium-ion battery state of charge estimation with a kalman filter based on an electrochemical model. In *2008 IEEE International Conference on Control Applications*, pages 702–707, 2008.
- [13] Satadru Dey, Beshah Ayalew, and Pierluigi Pisu. Nonlinear robust observers for state-of-charge estimation of lithium-ion cells based on a reduced electrochemical model. *IEEE Transactions on Control Systems Technology*, 23(5):1935–1942, 2015.
- [14] Long Cai and Ralph E White. Reduction of model order based on proper orthogonal decomposition for lithium-ion battery simulations. *Journal of The Electrochemical Society*, 156(3):A154–A161, 2009.
- [15] Xuebing Han, Mingao Ouyang, Languang Lu, and Jianqiu Li. Simplification of physics-based electrochemical model for lithium ion battery on electric vehicle. part ii: Pseudo-two-dimensional model simplification and state of charge estimation. *Journal of Power Sources*, 278:814–825, 2015.
- [16] Changfu Zou, Chris Manzie, and Dragan Nescic. A framework for simplification of pde-based lithium-ion battery models. *IEEE Transactions on Control Systems Technology*, 24(5):1594–1609, 2016.
- [17] Torben Jacobsen and Keld West. Diffusion impedance in planar, cylindrical and spherical symmetry. *Electrochimica Acta*, 40(2):255–262, 1995.
- [18] Kandler A. Smith, Christopher D. Rahn, and Chao-Yang Wang. Control oriented 1d electrochemical model of lithium ion battery. *Energy Conversion and Management*, 48:2565–2578, 2007.
- [19] Kandler A Smith, Christopher D Rahn, and Chao-Yang Wang. Model order reduction of 1d diffusion systems via residue grouping. *Journal of Dynamic Systems, Measurement, and Control*, 130(1):011012, 2008.
- [20] James L. Lee, Andrew Chemistruck, and Gregory L. Plett. One-dimensional physics-based reduced-order model of lithium-ion dynamics. *Journal of Power Sources*, 220(0):430–448, 2012.
- [21] James L. Lee, Andrew Chemistruck, and Gregory L. Plett. Discrete-time realization of transcendental impedance models, with application to modeling spherical solid diffusion. *Journal of Power Sources*, 206(0):367–377, 2012.
- [22] Albert Rodríguez, Gregory L. Plett, and M. Scott Trimboli. Fast computation of the electrolyte-concentration transfer function of a lithium-ion cell model. *Journal of Power Sources*, 360:642 – 645, 2017.
- [23] Albert Rodríguez and Gregory L. Plett. Controls-oriented models of lithium-ion cells having blend electrodes. part 2: Physics-based reduced-order models. *Journal of Energy Storage*, 11:219 – 236, 2017.
- [24] Albert Rodríguez, Gregory L Plett, and M Scott Trimboli. Improved transfer functions modeling linearized lithium-ion battery-cell internal electrochemical variables. *Journal of Energy Storage*, 20(April):560–575, 2018.
- [25] Albert Rodríguez, Gregory L. Plett, and M. Scott Trimboli. Comparing four model-order reduction techniques, applied to lithium-ion battery-cell internal electrochemical transfer functions. *eTransportation*, 1:100009, 2019.
- [26] Marc Doyle, Thomas F. Fuller, and John Newman. Modeling of Galvanostatic Charge and Discharge of the Lithium/Polymer/Insertion Cell. *Journal of The Electrochemical Society*, 140(6):1526 – 1533, 1993.
- [27] Thomas F. Fuller. Simulation and Optimization of the Dual Lithium Ion Insertion Cell. *Journal of The Electrochemical Society*, 141(1):1, 1994.
- [28] Gregory L. Plett. *Battery Management Systems, Volume I: Battery Modeling*. Artech House, 2015.
- [29] James L. Lee, Lukas L. Aldrich, Kirk D. Stetzel, and Gregory L. Plett. Extended operating range for reduced-order model of lithium-ion cells. *Journal of Power Sources*, 255:85–100, jun 2014.
- [30] Albert Rodríguez. Improvements to Fidelity, Generation and Implementation of Physics-Based Lithium-Ion Reduced-Order Models. PhD thesis, University of Colorado Colorado Springs, 2017 (<https://hdl.handle.net/10976/166734>).
- [31] Kirk D Stetzel. Model-Based Estimation of Battery Cell Internal Physical State. MSEE Thesis, University of Colorado Colorado Springs, 2014.
- [32] Kirk D. Stetzel, Lukas L. Aldrich, M. Scott Trimboli, and Gregory L. Plett. Electrochemical state and internal variables estimation using a reduced-order physics-based model of a lithium-ion cell and an extended Kalman filter. *Journal of Power Sources*, 278:490–505, mar 2015.
- [33] Gregory L. Plett. *Battery Management Systems, Volume II: Equivalent-Circuit Methods*. Artech House, 2015.

- [34] J Vetter, P Novák, MR Wagner, C Veit, K-C Möller, JO Besenhard, M Winter, M Wohlfahrt-Mehrens, C Vogler, and A Hammouche. Ageing mechanisms in lithium-ion batteries. *Journal of Power Sources*, 147(1–2):269–281, 2005.
- [35] Adam Smiley and Gregory L Plett. An adaptive physics-based reduced-order model of an aged lithium-ion cell , selected using an interacting multiple-model Kalman filter. *Journal of Energy Storage*, 19(July):120–134, 2018.
- [36] Adam J. Smiley, Willie K. Harrison, and Gregory L. Plett. Postprocessing the outputs of an interacting multiple-model kalman filter using a markovian trellis to estimate parameter values of aged Li-ion cells trellis to estimate parameter values of aged li-ion cells. *Journal of Energy Storage*, 27:101043, 2020.
- [37] E. Miguel. Electrochemical Model-Based Advanced Battery Control Systems. PhD thesis, Mondragon Goi Eskola Politeknikoa, 2020.
- [38] Anirudh Allam and Simona Onori. Online capacity estimation for lithium-ion battery cells via an electrochemical model-based adaptive interconnected observer. *IEEE Transactions on Control Systems Technology*, pages 1–16, 2020.




M. SCOTT TRIMBOLI (M'93–SM'19) received the B.S. degree in engineering science (distinguished graduate) from the United States Air Force Academy, Colorado Springs, CO in 1980 and the M.S. degree in engineering (Guggenheim fellow) from Columbia University, New York, NY in 1981. He received the Ph.D. degree in control systems engineering in 1989 from Oxford University, Oxford, United Kingdom.

From 1983 to 1986 and from 1989 to 1991 he served on the faculty of the Department of Astronautics at the United States Air Force Academy. From 1992 to 1994 he was an exchange scientist with the German Aerospace Research Establishment, (DLR) in Goettingen, Germany. He is currently Associate Professor of Electrical and Computer Engineering with the University of Colorado Colorado Springs. His research interests include: multivariable control theory, model predictive control, reduced-order modeling of lithium-ion battery cells and predictive methods for battery fast charge and state of power estimation.



E. MIGUEL received the master's and Ph.D. degrees in mechanic engineering and electric energy from Mondragon Unibertsitatea at Basque Country, Spain, in 2014 and 2020, respectively.

Since February 2020, he has been lecturer and researcher at Mondragon Unibertsitatea. His main research interests include battery physics-based models development and BMS algorithms development.



I. LOPETEGI received the B.S. degree in energy engineering and the M.S. in energy and power electronics from Mondragon Unibertsitatea, Arasate, in 2018 and 2020, respectively. He is currently pursuing the Ph.D. degree in electrical energy engineering at Mondragon Unibertsitatea.

His research interest includes physics-based reduced-order modeling of lithium-ion cells, modeling of aging mechanisms and state-of-charge and state-of-health estimation.



GREGORY L. PLETT (S'97–M'98–SM'02) received the B.Eng. degree in computer systems engineering (with high distinction) from Carleton University, Ottawa, in 1990 and the M.S. and Ph.D. degrees in electrical engineering from Stanford University, Stanford, CA, in 1992 and 1998, respectively.

He is currently Professor of Electrical and Computer Engineering with the University of Colorado Colorado Springs. His research includes: physics-

based reduced-order modeling of lithium-ion cells; system identification of physics-based model parameters; estimation of cell internal state; state-of-charge, state-of-health and state-of-life estimation; power and energy prediction. He is author of two books, *Battery Management Systems, Volume I: Battery Modeling* (Artech House, 2015) and *Battery Management Systems, Volume II: Equivalent-Circuit Methods* (Artech House, 2015).

Dr Plett is Life Member of the Electrochemical Society.



L. OCA received the degree in management engineering (End of Degree Awards for the best academic records) from Mondragon Unibertsitatea, Basque Country, Spain, in 2015 and the M.S. degrees in Industrial engineering from Mondragon Unibertsitatea in 2017. She received the Ph.D. degree in applied engineering from Mondragon Unibertsitatea in 2020.

She is currently a researcher and lecturer at Mondragon Unibertsitatea. Her research includes:

physics-based modelling of different electrochemical energy storage devices (i.e. lithium-ion batteries, sodium-ion batteries, lithium-ion capacitors), parameter measurement and identification of physics-based models and lithium-ion cell design fabrication and optimization through physics-based models.



U. IRAOLA received the B.Sc, M.Sc. and Ph.D. in electrical engineering from Mondragon Unibertsitatea, Spain, in 2006, 2009 and 2014 respectively.

He is currently a researcher and lecturer in the Department of Electronics and Informatics, Faculty of Engineering, Mondragon Unibertsitatea. His current research interests include power electronics modelling, energy storage modelling and control of energy storage systems via power electronic converters. He has participated in various

research projects in the fields of energy storage systems, renewable energy applications and projects related to elevator applications.



E. BEKAERT received her Master degree in chemistry from University Lille I, Villeneuve d'ascq, France in 2001 and her PhD in Materials science from the same university in 2004.

As a post-doc research fellow, she joined the Network of Excellence ALISTORE at the Institute of Condensed Matter Chemistry. Her research was dedicated to the applications of solid-state NMR to the structural and physicochemical characterization of Li-ion batteries materials. In 2008, she

joined ZSW-Zentrum für Sonnenenergie und Wasserstoff-Forschung, and worked on scaled-up synthesis for industrial partners. Under the supervision of Dr. Margret Wohlfahrt-Mehrens (ZSW), she joined in 2011 the Helmholtz Institut Ulm. In 2014, she became research line manager of Post mortem at the CIC energiGUNE, where her teams focus on the analyses of failure mechanism of Electrical Energy storage (EES) systems.

She is currently Group Lead of Ageing, Post mortem & Safety with CIC energiGUNE, Vitoria-Gasteiz, Spain. Her research focused on different topics related to safety and lifespan of batteries using invasive and non-invasive technics.

• • •